

# PureWaterCooler™

by VERTEX

## High Capacity 3-Temp Water Dispenser

*Bottle-less water dispenser with filtration provides hot, room and cold temperature water from your tap that is safe, clean and great tasting.*



### Offers

- Largest Hot and Cold tank capacities:  
1 gal Cold, 0.7 gal Hot, 2.2 gal Room temp
- Higher Capacity 75 GPD RO Filter System

### Features

- Three temperature system: Hot, Room and Cold
- Easy to use microprocessor control panel on front
  - Separate hot/cold power switches
  - Reboil switch to bring water to 212° F
  - Automatic heating control with over-temperature shut-off
- Built-in filtration system is easily accessed for replacement
  - Available with Reverse Osmosis filtration system
  - Or Standard Dual-Cartridge filtration system
- High efficiency sealed compressor cooling system with adjustable cold water thermostat, 37-50°F
- Stainless steel hot and cold water tanks
- Automatic float valve with solenoid shut-off
- Hot water faucet safety lock
- Available with ultraviolet sterilizer



Filter assembly is front panel accessible

### Specifications

Shipping Weight: 66 lb.  
 Dimension: 16"W x 16"D x 42"H  
 Floor to spigot: 30"  
 Spigot to Drip Tray: 7.5"  
 Cold tank volume 1 gal  
 Hot tank volume .7 gal  
 Room Temp tank volume 2.2 gal  
 Cooling Rate: 1.5 gal/hr 37-50 °F  
 Heating Rate: 1.5 gal/hr 185 °F  
 Voltage: 100-120 volts, 50/60 hz  
 Power Required: 600w

### Filter System

Standard Filter **3000F**  
**Stage 1:** 5 micron Sediment  
**Stage 2:** 10 micron Activated Carbon  
 Reverse Osmosis Filter **3000R**  
 Above 2 stages plus  
**Stage 3:** 75-GPD RO Membrane  
 Automatic tank full control  
 Fully assembled  
 - connection hardware included

Meets Energy Star Requirements 

### ORDERING INFORMATION

3-Temp Model with Reverse Osmosis	<b>PWC-3000R</b>
3-Temp Model with Standard Filtration	<b>PWC-3000F</b>
With UV stage	add /UV
Leak detector option	<b>LC-8021</b>
Cup holder	<b>CPH-1207</b>
Replacement Filters	
Sediment	<b>IFA-4035</b>
GAC Carbon	<b>IFA-4034</b>
RO membrane, 75 GPD	<b>MH-4206</b>

Authorized Dealer

